



V85 Strada - TECHNICAL SPECIFICATION	
Engine	Transversal 90° V-Twin, two valves per cylinder with variable timing (titanium intake valves), air cooled, Ride by Wire
Displacement	853 cc
Bore and stroke	84 x 77 mm
Max. power	80 Hp @ 7,750 rpm
Max. torque	83 Nm @ 5,100 rpm
Gearbox	6 speed
Front suspension	Ø 41 mm USD fork with adjustable preload and rebound damping. 170 mm wheel travel
Rear suspension	Lateral monoshock with adjustable preload and rebound damping. 170 mm wheel travel
Front brake	Twin Ø 320 mm floating discs, 4-piston Brembo monobloc radial calipers
Rear brake	Single Ø 260 mm disc, 2-piston caliper
Front wheel	Cast aluminium, 19" x 2.5"
Rear wheel	Cast aluminium, 17" x 4.25"
Seat height	830 mm
Dry weight	205 Kg
Wet weight*	226 Kg
Fuel tank	23 litre
Consumption	4.9 L/100 Km
CO₂ Emissions	119 g/Km
Compliance	Euro 5+
Equipment	Full LED headlight with DRL, LED indicators, ABS and Traction Control, Cruise Control, 3 Riding Modes, full colour TFT instrument, USB socket, manually adjustable windscreen, low mudguard

*According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume